according to Regulation No. 1907/2006

PRODUCT No.: **PRODUCT NAME:**

TS4A005 **BLACK INK**



Report Date: 2008.03.03 Revision Date: 2008.03.05

1. Identification of the substance/preparation and company/undertaking

Product No: Product name: **TS4A005 Black ink**

Application: inkjet printing ink

Manufacturer: EBS Ink-Jet Systeme GmbH

Address: Alte Ziegelei 19-25

D-51588 Nűmbrecht - Elsenroth

Phone number: +49(0)2293/939-0 +49(0)2293/939-3 Telefax: mail@ebs-inkjet.de E-Mail:

Emergency telephone: Resuscitation Centre of the Free University of Berlin

telephone: +49 (0) 30 3035-3466

2. Hazards identification

Classification: Highly flammable, irritant.

Physical and chemicals hazards: Highly flammable.

Irritating to eyes. Repeated exposure may cause skin dryness **Human health hazards:**

or cracking. Vapours may cause drowsiness and dizziness.

Environmental hazards: Mix with water – migrates easily in ground and water environments.

3. Composition/information on ingredients

Component name	CAS-No.	WE-No.	Content [%]	Classification
Acetone	67-64-1	200-662-2	60-85 %	F; R:11 Xi; R: 36-66-67
Cyclohexanon	108-94-1	203-631-1	5-10 %	Xn R: 10-20
Amines, C12-14-tert-alkyl, compds. with 1-[[5-(1,1-dimethylpropyl)-2-hydroxy-3-nitrophenyl]azo]-2-naphthalenol 1-[[2-hydroxy-4(or 5)-nitrophenyl]azo]-2-naphthalenol chromium complex	117527-94-3	403-720-7	_	N; R51-53

The full text for all R-Phrases are displayed in section No.16.

4. First aid measures

General hints: Carry the victim out of the hazardous area and lay them down.

Should respiration become irregular or standstill, give artificial respiration. If the clothing is contaminated with the product, take it

off immediately.

Eye contact: Rinse wide open eyes with running water for a few minutes

and consult doctor.

Skin contact: Take off contaminated clothing and wash affected spots on the skin

with soap and a lot of water; do not use any solvents.

Ingestion: Make the victim drink a lot of water – consult a doctor immediately. Inhalation: Harmful by inhalation. Ensure a supply of fresh air - if the suffering

persists, consult a doctor.

₽ 1 **1** 4

according to Regulation No. 1907/2006

PRODUCT No.: PRODUCT NAME:

TS4A005 BLACK INK



5. Fire-fighting measures:

Fire extinguishing agents: fire powder, carbon dioxide (CO₂), foam, sprayed water jet.

Hazardous decomposition products: CO, CO₂ in the case of fire.

6. Accidental release measures:

Personal precautions :	Splash goggles. Full suit. Vapour respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product.
Environmental precautions and cleanup methods :	Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with dry earth, sand or noncombustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed.

7. Handling and storage:

Handling:	Do not eat or drink while handling the product. Handle the product with care and keep clean. Avoid contact with eyes. Do not inhale the vapours. Keep containers in a well ventilated room and away from ignition sources.
Explosion Hazard:	Do not smoke. Take action to protect it against static electricity.
Storage:	Protect against heat and exposure to sun radiation in compliance with Inflammable Fluid Regulations. Store in a cool place, otherwise pressure may rise and a risk of disruption occur

8. Exposure controls/personal protection:

Exposure limits according to Hazardous Material Regulations:

Compound	MAK [mg/m³]
Acetone	600
Cyclohexanon	40

Airways protection: Ensure good ventilation if major amounts of the product are used.

Hand protection: Wear solvent resistant gloves of latex or the like.

Eye protection: Wear tight protective glasses.

9. Physical and chemical properties:

State and appearance:fluidColour:blackSmell:ketone-likeExplosion limits:lower: 2,5 %Vol.

upper: 13 %Vol.

pH: n.a.

Boiling point: 56℃ at 1013 hPa Vapour pressure: 247 hPa / 20℃

Auto-ignition point: 540° C Ignition point: $< -20^{\circ}$ C

Water solubility: partially miscible

Organic solvent solubility: miscible with almost all such solvents

1 4

according to Regulation No. 1907/2006

PRODUCT No.: PRODUCT NAME:

TS4A005 BLACK INK



10. Stability and reactivity:

Stability: The product is stable.

Thermal decomposition: no decomposition occurs, if it is stored and handled appropriately.

Hazardous decomposition products: CO, CO₂ in the case of fire.

Hazardous reactions: no hazardous reactions, if it is used for purposes it is designed for

application.

11. Toxicological information:

Compound	Toxicological information
Acetone	LD ₅₀ Oral Rat: 4050 mg/kg
	LD ₅₀ Oral Mouse : 3000 mg/kg
Cyclohexanon	LD ₅₀ Oral Mouse: 1400 mg/kg

Inhalation: Harmful by inhalation. Vapour concentration exceeding exposure

limits can cause dizziness and headache and can affect the central

nervous system.

Contact with skin: Irritation can occur. Longer or repeated contact with skin makes the

skin lose natural fat and can cause dermatitis.

12. Ecological information:

Poses a hazard to water if major amounts infiltrate into ground or surface water. Do not allow it to get into a sewerage system; an explosion hazard can occur.

Mobility:no data availableBioaccumulative potential:no data availableResults of PBT assessment:no data available

13. Disposal considerations:

Waste code: 08 03 12* - Printing ink waste products which contain dangerous material.

The waste code numbers are recommendations based on standard use. For special use or disposal, other waste code numbers may be applicable. Observe respective environment regulations.

14. Transport information:

14.1. By road

Class / Packing Group: 3 / II UN No.: UN 1210 Transport Description: UN 1210

Sign:



14.2. By sea

Class / Packing Group: 3 / II UN No.: UN 1210

Transport Description: Printing ink related material

Sign:



a 4

according to Regulation No. 1907/2006

PRODUCT No.: PRODUCT NAME:

TS4A005 BLACK INK



14.3. By air

Class / Packing Group: 3 / II UN No.: UN 1210

Transport Description: Printing ink related material

Sign:



15. Regulatory information:



F Highly flammable



Xi Irritant

Contains: Acetone

R-Phrases: R 36 Irritating to eyes

R 52 Harmful to aquatic organisms

R 53 May cause long-term adverse effects in the aquatic

environment

R 66 Repeated exposure may cause skin dryness or cracking

R 67 Vapours may cause drowsiness and dizziness

S-Phrases: S 2 Keep out of the reach of children

S 9 Keep container in a well-ventilated place

S 16 Keep away from sources of ignition – no smoking

S 26 In case of contact with eyes, rinse immediately with plenty of water

and seek medical advice

S 33 Take precautionary measures against discharges

S 43 In case of fire use CO₂ (carbon dioxide) and foam extinguisher

Class as per Inflammable Fluid Regulations: A I

16. Other information:

R 10	Flammable
R 11	Highly flammable
R 20	Harmful by inhalation
R 36	Irritating to eyes
R 51	Toxic to aquatic organisms
R 53	May cause long-term adverse effects in the aquatic environment
R 66	Repeated exposure may cause skin dryness or cracking
R 67	Vapours may cause drowsiness and dizziness

MSDS has been produced on the basis of the following documents:

Dangerous Preparations Directive 1999/45/EC, Directive 67/548/EWG and REACH-Regulation No. 1907/2006.

The data is based on the current state of our knowledge.

Nevertheless it should not be considered a promise of product properties or make grounds for any legal relation.

a 4