



World Class Printing Systems for **Real World Applications**

MORE OPTIONS FOR MAKING YOUR MARK

Squid Ink's SQ-10 and SQ-30 laser coding systems are designed for high speed food and beverage, pharmaceutical, cosmetic, and other primary coding applications. Squid Ink lasers can permanently mark onto paper, cardboard, plastic, glass, wood, coated metal, leather, and more. Users select between a 10W (SQ-10) and 30W system (SQ-30) depending on their specific application requirements.

APPLICATION VERSATILITY

- Permanent coding of text, time and date, bar codes, serial numbering and more
- Quick and easy installation for both stationary and moving products
- Easily fits into production environments where space is limited
- Laser head can be rotated 90° in less than 5 minutes

RELIABLE AND ECONOMICAL

- No ink/consumables for lower cost of ownership
- Clean and eco-friendly coding system
- Rugged cast aluminum controller body
- IP54 rating ensures maximum reliability and uptime in demanding applications
- Integrated key switch and interlock relay for increased safety on the production floor

HIGH QUALITY CODE GENERATION

- Scribing technology produces non-dot matrix, razor sharp marks on a variety of substrates
- Ability to mix different fonts and logos in a single message
- Discrete coding ability for anti-counterfeiting and traceability
- Ideal coding alternative where CIJ systems are not practical

EASY TO START, SIMPLE TO RUN


- All-in-one design for fast installation and line changes
- Easy to use touchscreen software built right into controller
- Intuitive system includes focus finder and code area preview window on product during setup
- Easily configurable in a variety of angles with optional mobile stand

THE RIGHT SOLUTION

Rugged design. High quality coding. Low cost of ownership. Your benefits go on and on. When it comes to industrial laser coding, rely on Squid Ink to provide the right solution for your coding and marking needs.







2) An optional heavy duty stand is available to simplify setup and install the system in a variety of configurations.









3) The laser head can be rotated 90 degrees in less than 5 minutes.

4) An integrated key switch and interlock relay is included for safety on the production floor.

SYSTEM SPECIFICATIONS

- Print Technology CO2 laser coding system, full sealed RF-excited metal tube
- Laser Wavelength 10.6µm
- Laser Galvanometer High-precision 2D high-speed scanning galvanometers
- Cooling Method Atmospheric air-cooled
- Dust Way Sealed
- **Power Consumption -** 500W-1000W (110VAC, 60Hz)
- Marking Focal Length 100mm 190mm (133mm currently on SQ-10 & SQ-30)
- Positioning Accuracy 0.01mm
- Minimum Line Width 0.1mm
- **Marking Area -** 50mm X 50mm 175mm X 175mm
- Assembly Line Speed Support <120m/min
- Marking Speed 800 1000 characters/second
- Character Size Adjustable in marking range
 Marking Line Number Code Rotation 0 to 360°
- Software Features Counter, lot counter, shift code, time and date, bar codes, expiration date
- Operating Languages English and Chinese
- Cabinet Construction Heavy duty cast aluminum
- SQ-10 Cabinet Dimensions 29" (74cm) L x 6.25" (16cm) W x 7.25" (19cm) H
- SQ-30 Cabinet Dimensions 29" (74cm) L x 5.375" (14cm) W x 7.5" (19cm) H
- SQ-30 Power Controller Dimension 13" (33cm) L x 5.5" (14cm) W x 10.25" (26cm) H
- Electrical Requirements 90 240 VAC, 50/60Hz
- Operating Environment $40^{\circ}F$ $105^{\circ}F$ ($5^{\circ}C$ $40^{\circ}C$)
- **Humidity Range -** 10 90% relative humidity, non-condensing
- Packaged Weight SQ-10: 56 lbs. (25kg); SQ-30: 67 lbs. (30kg)

OPTIONAL ACCESSORIES

- Print Trigger Optical, fiber optic, ultrasonic, laser, metal proximity, capacitive proximity
- Encoder For operation with variable speed conveyors
- Mobile Stands Heavy duty stand with ability to rotate laser controller in any direction and easily raise and lower marking machine by a single operator; includes casters for easy transportation within plant
- Installation and Training On-site installation and training available



©2017 Squid Ink Manufacturing, Inc. Specifications subject to change. All trademarks are the property of their registered owners.



